



Passenger car engine oils - Fully Synthetic

Eurol Elance 5W-30

Fully synthetic fuel economy engine oil, ACEA C3/C2 and Renault RN17

Beschreibung

Eurol Elance 5W-30 is a fully synthetic high performance engine oil for gasoline and diesel vehicles.

Eurol Elance 5W-30 provides an extremely stable lubricant film at the cold start and offers high thermal stability under severe driving operating conditions (motorway and urban traffic). The oil is able to flow and to lubricate critical parts, preventing wear and ensuring engine protection.

Eurol Elance 5W-30 provides maximum protection against rust and corrosion, while the used additive package keeps the engine clean and well lubricated.

Eurol Elance 5W-30 has low sulphated ash contents and also low levels of phosphor and sulphur (so called "mid-SAPS" technology).

Eurol Elance 5W-30 is suitable for use in applications where Renault RN17 is prescribes as well as applications where RN0700 and RN0710 are prescribed.

Approved

• API SN

Performance level

- ACEA C2
- ACEA C3
- VW 505.01
- MB 229.51
- MB 229.52MB 229.31
- BMW Longlife-04
- GM dexos 2
- VW 505.00
- OV 040 1547 D30

Recommended for use

- Renault RN0700 / 0710
- Renault RN17
- Dexos D

Physikalische Eigenschaften

injunancene Eigeneenancen		
Farbe	braun	
Dichte bei 20°C	0.851 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	73.2 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	12.1 cSt	ASTM D 445
Viskositätsindex	163	ASTM D 2270
Viskosität, dynamisch (CCS)	5832 cP	ASTM D 5293
Base number	8.0 mg	ASTM D 2896
Sulfatasche	0.78 wt%	ASTM D 874
Flammpunkt	200 °C	ASTM D 93
Stockpunt	-36 °C	ASTM D 97

Artikelnummer E100012 Version 9.0, 15-09-2022