



Eurol Elance FE 0W-20

Fuel economy, fully synthetic engine oil for certain Renault vehicles

Beschreibung

Eurol Elance FE 0W-20 is a full synthetic mid SAPS engine oil, especially formulated to meet the RN 17 FE specification. This oil is applicable to certain petrol engines as well as diesel engines (Euro 6d as from mid 2018) from Renault and Dacia. This engine oil is also suitable for vehicles where ACEA C5 is prescribed. Please note this oil is NOT backward compatible to other Renault specifications as RN 17, RN 17 RSA, RN 700, RN 710 and RN 720.

Eurol Elance FE 0W-20 is a low viscosity engine oil, that contributes to fuel efficiency without compromising wear protection, even under high temperatures during extended drain intervals. Further, this oil provides fast lubrication under cold weather conditions and at start-stop situations.

Eurol Elance FE 0W-20 offers excellent protection against deposits and sludge during its service life. Excellent thermal- and oxidation stability prevent the oil from alteration. Catalytic converters and particle filters are extremely well protected by this well balanced mid SAPS oil.

Eurol Elance FE 0W-20 is a shear stable engine oil formulation with low evaporation and good cold-start ability.

For certain severe applications, such as very often stop-and-go or extreme heavy loads, drain intervals should be reduced significantly, as being mentioned in some manuals. If the quality needed for a specific vehicle is not mentioned under the specification mentioned below, the applicability of this oil should be checked, in the manufacturers advice, or in the Eurol Product Advisor on www.eurol.com

Performance level

- ACEA C5
- Renault RN17 FE

Physikalische Eigenschaften

Farbe	Bernsteinfarb		
Dichte bei 20°C	0.84 kg/L	ASTM D 4052	
Viskosität, kinematisch bei 40°C	39 cSt	ASTM D 445	
Viskosität, kinematisch bei 100°C	8.2 cSt	ASTM D 445	
Viskositätsindex	190	ASTM D 2270	
Base number	8.7 mg	ASTM D 2896	
Flammpunkt	220 °C	ASTM D 93	
Stockpunt	-48 °C	ASTM D 97	

Artikelnummer E100014

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.