



Passenger car engine oils - Mineral

# **Eurol Special 15W-40**

Mineral motor oil for gasoline, LPG and diesel engines

#### **Beschreibung**

Eurol Special Multigrades are motor oils, formulated with shear-stable viscosity improvers to prevent viscosity drops after some time. Because of this, a strong and stable lubricant film is guaranteed, even at high temperatures.

Eurol Special Multigrades contain deterging and dispersing additives, keeping the oil and the engine clean, even the most critical parts. Corrosion and sludge are reduced to a minimum, while anti-wear additives, together with the high quality base oils, offer maximum protection to heavily loaded parts.

Eurol Special Multigrades have a long life-time and assure a low oil consumption. This oil can be used in all gasoline and LPG engines, as well in light duty, non-turbo charged diesel engines.

Eurol Special Multigrades are especially suitable for older cars as running-in motor oil.

### Performance level

• API SF/CD

#### Recommended for use

- MIL-L-2104D
- MIL-L-46152C

## Physikalische Eigenschaften

| injundance in Eigeneen and in     |            |             |
|-----------------------------------|------------|-------------|
| Farbe                             | braun      |             |
| Dichte bei 20°C                   | 0.867 kg/L | ASTM D 4052 |
| Viskosität, kinematisch bei 40°C  | 105.6 cSt  | ASTM D 445  |
| Viskosität, kinematisch bei 100°C | 14.4 cSt   | ASTM D 445  |
| Viskositätsindex                  | 140        | ASTM D 2270 |
| Viskosität, dynamisch (CCS)       | 5058 cP    | ASTM D 5293 |
| Base number                       | 8.0 mg     | ASTM D 2896 |
| Sulfatasche                       | 1.2 wt%    | ASTM D 874  |
| Flammpunkt                        | 220 °C     | ASTM D 93   |
| Stockpunt                         | -30 °C     | ASTM D 97   |

Artikelnummer E100020 Version 3.0, 12-04-2018