



Passenger car engine oils - Semi-synthetic

Eurol TurboCat 15W-40

Universal semi-synthetic Motor oil

Beschreibung

Eurol Turbocat 15W-40 is a semi-synthetic engine oil recommended for petrol and diesel engines. Because of the high viscosity index, the oil assures an excellent cold start as well as an excellent lubricating film with high temperatures.

Eurol Turbocat 15W-40 takes care of trouble free functioning of the engine, because of the chosen additive package. The oil helps reducing the fuel consumption as well as reducing emission levels.

Because of the unique formulation a low evaporation under severe operating conditions is guaranteed. In addition, Eurol Turbocat 15W-40 gives optimum protection against wear and has strong anti -corrosion and anti-foam characteristics as well as a high resistance against oxidation.

Together with the excellent detergent/dispersant properties, this oil ensures a clean and reliable engine.

Performance level

API SL/CF

Recommended for use

- ACEA A3/B3
- MB 229.1
- VW 501.01
- VW 505.00

Physikalische Eigenschaften

Farbe	braun	
Dichte bei 20°C	0.867 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	109.3 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	14.4 cSt	ASTM D 445
Viskositätsindex	134	ASTM D 2270
Viskosität, dynamisch (CCS)	6124 cP	ASTM D 5293
Base number	8.0 mg	ASTM D 2896
Sulfatasche	0.9 wt%	ASTM D 874
Flammpunkt	214 °C	ASTM D 93
Stockpunt	-30 °C	ASTM D 97

Artikelnummer E100022 Version 1.4, 22-10-2020