



Heavy duty diesel engine oils - Mineral

# **Eurol Multifleet 10W-30**

### Mineral motor oil for mixed fleet

# **Beschreibung**

Eurol Multifleet 10W-30 has been developed according to the latest oil consumption and exhaust emission requirements and protects against oil thickening and wear. Besides, it has an excellent deterging capability.

Eurol Multifleet 10W-30 is especially suitable for mixed fleet applications like gasoline, LPG and light loaded diesel engines, whether or not turbo charged and/or with catalytic converter. Because of this broad applicability, this oil can reduce the stock level for the fleet owner and the retailer.

Eurol Multifleet 10W-30 amply fulfils the latest, strict norms regarding deposits on piston crowns, in top piston ring grooves and on the rest of the pistons.

## Performance level

• API SJ/CG-4

#### Recommended for use

- API CF
- ACEA A2/B2
- ACEA A3/B3
- ACEA E2
- Allison C-4
- MB 228.1
- MAN 271
- Volvo VDS
- MTU type 2
- VW 505.00 (97)
- VW 501.01
- Mack EO/L

#### Physikalische Eigenschaften

injundance in Eigeneen and in		
Farbe	braun	
Dichte bei 20°C	0.86 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	75 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	11.8 cSt	ASTM D 445
Viskositätsindex	152	ASTM D 2270
Viskosität, dynamisch (CCS)	4781 cP	ASTM D 5293
Base number	8.4 mg	ASTM D 2896
Sulfatasche	1.18 wt%	ASTM D 874
Flammpunkt	206 °C	ASTM D 93
Stockpunt	-39 °C	ASTM D 97

Artikelnummer E100032 Version 6.0, 11-01-2022