



Passenger car engine oils - Fully Synthetic

## Eurol Super Ultra II 0W-30

Fully synthetic long-life motor oil VW 503.00, 506.00 and 506.01

### Beschreibung

Eurol Super Ultra II 0W-30 is a fully synthetic motor oil for gasoline and diesel engines, in passenger cars and light duty commercial vehicles of Volkswagen, Audi, Seat and Skoda. Operating according the so called WIV ( prolonged drain interval) system, drain intervals can go up to 50.000 km for diesel engines and up to 30.000 km for gasoline engines.

Eurol Super Ultra II 0W-30 meets the requirements for prolonged drain intervals of Volkswagen (503.00 for gasoline, 506.00 for diesel, 506.01 for pump discharge nozzle diesel) for their latest models (year 2000 and up) and therefore reduces the number of oils to keep in stock. Eurol Super Ultra II 0W-30 provides an extremely rapid and stable lubricant film at the cold start and a high thermal stability.

Also because of the very low evaporation tendency under heavy duty operating conditions, oil consumption is negligible.

Eurol Super Ultra II 0W-30 has fuel saving properties and can be mixed with both synthetic and mineral oils. For technical reasons, Volkswagen does not recommend this oil for cars without a prolonged drain interval system.

NB: This oil is not recommended for certain special Audi turbo charged gasoline engines for which VW 503.01 is prescribed. For this application both Eurol® Synergy 0W-30 and 0W-40 are the right choice.

### Performance level

- VW 503.00
- VW 506.00
- VW 506.01

### Physikalische Eigenschaften

Farbe	Gelb bis klar	
Dichte bei 20°C	0.854 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	53.5 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	9.5 cSt	ASTM D 445
Viskositätsindex	173	ASTM D 2270
Flammpunkt	210 °C	ASTM D 93
Stockpunkt	-36 °C	ASTM D 97

Artikelnummer E100063  
Version 2.0, 12-02-2018

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.