



Passenger car engine oils - Fully Synthetic

Eurol Synergy 0W-40

Fully synthetic fuel economy long-life motor oil MB 229.5

Beschreibung

Eurol Synergy 0W-40 is a fully synthetic motor oil for use in passenger cars and light duty commercial vehicles. This oil can be used in cars with turbo charged engines, catalytic converters and direct fuel injection diesel engines.

Eurol Synergy 0W-40 provides an extremely rapid and stable lubricant film at the cold start and maintains this film at high operating temperatures

Next to this, this oil offers an extremely high oxidation stability and wear protection. Both engine and oil stay clean, even after prolonged drain intervals (up to 30.000 km).

Eurol Synergy 0W-40 offers extra fuel saving properties and can be mixed with both synthetic and mineral motor oils, although especially for this oil, mixing with other oils will not benefit the outstanding quality of the products.

Eurol Synergy 0W-40 meets the MB 229.5 specification and can be used for an intensive and prolonged use.

Approved

- API SN

Performance level

- ACEA A3/B4
- VW 502.00
- MB 229.5
- MB 229.3
- BMW Longlife-01
- Porsche A40
- Renault RN0710
- Renault RN0700
- Ford WSS-M2C937-A
- VW 505.00

Recommended for use

- Fiat 9.55535-Z2
- Fiat 9.55535-N2
- Fiat 9.55535-M2
- Fiat 9.55535-H2

Physikalische Eigenschaften

Farbe	braun	
Dichte bei 20°C	0.841 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	73.5 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	13.1 cSt	ASTM D 445
Viskositätsindex	182	ASTM D 2270
Viskosität, dynamisch (CCS)	5260 cP	ASTM D 5293
Sulfatasche	1.09 wt%	ASTM D 874
Flammpunkt	207 °C	ASTM D 93
Stockpunt	-45 °C	ASTM D 97

Artikelnummer E100064
Version 3.0, 19-03-2021

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.