



Motorcycle oils 4T - Fully Synthetic

Eurol Sportbike 5W-50

Fully synthetic motor oil for 4-stroke motorcycles

Beschreibung

Eurol Sportbike 5W-50 Full Synthetic is a fully synthetic engine oil and contains a dedicated ester technology to provide extra protection against wear, deposits, sludge and oxidation under all conditions.

This oil can also be used in motorcycle transmissions where an API SF, SG, SH, SJ or SL oil is prescribed.

Eurol Sportbike 5W-50 Full Synthetic is suitable for touring, racing, as well as for cross applications, under all conditions.

Eurol Sportbike 5W-50 Full Synthetic offers an excellent protection against wear, deposits, sludge and oxidation. Even under the most severe operating conditions air-absorption and foam building are minimised. Eurol Sportbike 5W-50 Full Synthetic has a very low volatility by which oil thickening and oil consumption are reduced to a minimum. Due to the special formulation, this oil offers excellent protection to gearboxes and wet disc clutches.

Even under the extreme conditions in gearboxes, the selected oil thickener will hardly break down so that at high temperatures the viscosity stays in grade to guarantee a solid lubricant film.

At low temperatures Eurol Sportbike Full Synthetic 5W-40 and 5W-50 rapidly provide a solid lubricant film for an optimum protection of the engine at cold starts.

Approved

- JASO MA2

Performance level

- API SN
- JASO MA

Physikalische Eigenschaften

Farbe	braun	
Dichte bei 20°C	0.851 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	120.5 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	19.6 cSt	ASTM D 445
Viskositätsindex	185	ASTM D 2270
Viskosität, dynamisch (CCS)	6100 cP	ASTM D 5293
Flammpunkt	210 °C	ASTM D 93
Stockpunkt	-48 °C	ASTM D 97

Artikelnummer E100081
Version 3.0, 11-03-2021

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.