



Passenger car engine oils - Fully Synthetic

# **Eurol Super Lite 5W-50**

Fully synthetic oil for gasoline and diesel engines, with or without turbo

## **Beschreibung**

Eurol Super Lite 5W-50 is a fully synthetic motor oil for gasoline and diesel engines in passenger cars and light duty commercial vehicles. This oil can be applied for cars equipped with catalytic converters, turbo charged engines and for direct fuel injection systems.

Eurol Super Lite 5W-50 provides an extremely quick and stable lubricant film at the cold start and offers high thermal stability under heavy duty operating conditions.

Eurol Super Lite 5W-50 not only offers extremely good wear protection, but also protects against rust and corrosion, while special additives keep all parts free from dirt, sludge and deposits.

Eurol Super Lite 5W-50 offers fuel saving properties and can be mixed with both synthetic and mineral motor oils.

### Performance level

API SN/CF

# Recommended for use

- ACEA A3/B4
- VW 502.00
- MB 229.3
- Renault RN0710
- Renault RN0700
- VW 505.00

#### Physikalische Eigenschaften

i ilyontanoono Eigonoonatton		
Farbe	braun	
Dichte bei 20°C	0.849 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	119.9 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	19.6 cSt	ASTM D 445
Viskositätsindex	186	ASTM D 2270
Viskosität, dynamisch (CCS)	4983 cP	ASTM D 5293
Base number	10.4 mg	ASTM D 2896
Sulfatasche	1.31 wt%	ASTM D 874
Flammpunkt	200 °C	ASTM D 93
Stockpunt	-39 °C	ASTM D 97

Artikelnummer E100093 Version 1.2, 07-06-2021