



Motorcycle oils 4T - Mineral

Eurol 4T Road 10W-40

Mineral motor oil for 4-stroke motorcycles

Beschreibung

Eurol 4T Road 10W-40 is a mineral engine oil without friction modifiers and has been especially developed for 4-stroke motorcycles. This oil can also be used in motorcycle transmissions where an API SG oil is prescribed.

Eurol 4T Road 10W-40 is suitable for touring, racing, as well as for cross applications, under all conditions.

Eurol 4T Road 10W-40 offers an excellent protection against wear, deposits, sludge and oxidation. Even under the most severe operating conditions air-absorption and foam building are minimised.

Eurol 4T Road 10W-40 has a very low volatility by which oil thickening and oil consumption are reduced to a minimum. Due to the special formulation, this oil offers excellent protection to gearboxes and wet disc clutches.

Even under the extreme conditions in gearboxes, the selected oil thickener will hardly break down so that at high temperatures the viscosity stays in grade to guarantee a solid lubricant film.

Performance level

- API SL/CF
- JASO MA
- JASO MA2

Physikalische Eigenschaften

Farbe	braun	
Dichte bei 20°C	0.87 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	105 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	14.9 cSt	ASTM D 445
Viskositätsindex	147	ASTM D 2270
Viskosität, dynamisch (CCS)	6463 cP	ASTM D 5293
Flammpunkt	205 °C	ASTM D 93
Stockpunt	-45 °C	ASTM D 97

Artikelnummer E100098 Version 2.0, 05-03-2024