



Passenger car engine oils - Semi-synthetic

## Eurol Pro Lite 15W-40

Semi-synthetic motor oil for passenger cars and light duty commercial vehicles

### Beschreibung

Eurol Pro Lite 15W-40 is a semi-synthetic motor oil with a universal applicability in gasoline and diesel engines in passenger cars and light duty commercial vehicles. This oil provides a good lubricant film at both low and high operating temperatures.

Eurol Pro Lite 15W-40 enables the engine to perform under all conditions due to its special additive package, meeting both European and American standards. Also fuel savings and exhaust emission reduction can be obtained with this product. Because of the unique formulation, the oil has a low evaporation tendency, minimizing oil consumption.

Eurol Pro Lite 15W-40 offers excellent protection against wear, foam build-up and corrosion. Together with deterging and dispersing properties, this oil will keep the engine clean and in a optimum condition.

Because of the high temperature stability, Eurol Pro Lite 15W-40 will maintain its quality level and will not thicken.

Eurol Pro Lite 15W-40 is not compatible with diesel vehicles equipped with a DPF.

### Performance level

- API SN/CF
- ACEA A3/B4
- MB 229.1
- VW 501.01
- VW 505.00

### Physikalische Eigenschaften

|                                   |            |             |
|-----------------------------------|------------|-------------|
| Farbe                             | braun      |             |
| Dichte bei 20°C                   | 0.864 kg/L | ASTM D 4052 |
| Viskosität, kinematisch bei 40°C  | 101 cSt    | ASTM D 445  |
| Viskosität, kinematisch bei 100°C | 14.9 cSt   | ASTM D 445  |
| Viskositätsindex                  | 153        | ASTM D 2270 |
| Viskosität, dynamisch (CCS)       | 3377 cP    | ASTM D 5293 |
| Base number                       | 10.4 mg    | ASTM D 2896 |
| Sulfatasche                       | 1.31 wt%   | ASTM D 874  |
| Flammpunkt                        | 190 °C     | ASTM D 93   |
| Stockpunt                         | -39 °C     | ASTM D 97   |

Artikelnummer E100135  
Version 1.2, 18-09-2020

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.