



Passenger car engine oils - Fully Synthetic

Eurol Ultrance VA 0W-30

Fuel economy, fully synthetic oil for diesel and gasoline engines

Beschreibung

Eurol Ultrance VA 0W-30 is a long-life, 'full saps', fully synthetic based oil formulation. Eurol Ultrance VA 0W-30 has a universal applicability in certain modern engines Euro-4, Euro-5 and Euro-6, diesel or gasoline, naturally aspirated or turbocharged, indirect or direct injection, requiring SAE 0W-30 with ACEA A5/B5 and API SL specifications.

Eurol Ultrance VA 0W-30 enables the engine to perform under all operating conditions (motorway and urban traffic) due to its special additive package.

Eurol Ultrance VA 0W-30 provides excellent performance in piston cleanliness, in reducing the formation of sludge and in keeping the turbocharger clean. Also improved fuel economy (min 5% in comparison with a mineral SAE 15W-40) and low emission reduction for powerful engines can be obtained with this product. Because of the unique formulation, the oil has a low evaporation tendency, minimizing oil consumption.

Eurol Ultrance VA 0W-30 offers low temperature properties for cold weather starting allowing easy starts and optimal lubrication of the engine. Eurol Ultrance VA 0W-30 is suitable for long oil change intervals and high engine loads according to the manufacturer's instructions.

Eurol Ultrance VA 0W-30 is recommended for the recent engines (B5, B6, B8, D5, D82 and D87 from Volvo) powered with turbo diesel or gasoline engines requiring fuel economy lubricants (ACEA A1/B1 or ACEA A5/B5, e.g. Land Rover TD5 and 3.2 gasoline, Honda 1.8L and 2.0L gasoline engines). Eurol Ultrance VA 0W-30 is also recommended for the 5-cylinder gasoline and diesel engines requiring the Volvo VCC 95200377 specification.

Physikalische Eigenschaften

Farbe	braun	
Dichte bei 20°C	0.842 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	53.8 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	10.2 cSt	ASTM D 445
Viskositätsindex	181	ASTM D 2270
Viskosität, dynamisch (CCS)	5740 cP	ASTM D 5293
HTHS	3 cP	CEC CL 23
Base number	9.8 mg	ASTM D 2896
Sulfatasche	1.1 wt%	ASTM D 874
Flammpunkt	200 °C	ASTM D 93
Stockpunkt	-48 °C	ASTM D 97

Approved

- API SL
- Volvo VCC 95200377

Performance level

- ACEA A5/B5

Recommended for use

- API CF

Artikelnummer E100158
Version 3.0, 06-10-2022

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.