



Passenger car engine oils - Fully Synthetic

Eurol Ultrance ST 5W-30

Fully synthetic mid SAPS engine oil for gasoline and diesel engines

Beschreibung

Eurol Ultrance ST 5W-30 is a fully synthetic, fuel-saving motor oil for gasoline and diesel engines, specifically developed for the latest models of passenger cars from the Stellantis group, including Peugeot, Citroen, Opel, and light commercial vehicles from Toyota.

Eurol Ultrance ST 5W-30 quickly establishes a stable lubricating film during cold starts and offers high thermal stability under extremely demanding operating conditions. Additionally, Eurol Ultrance ST 5W-30 has optimal dispersing and detergency capabilities, keeping the engine clean.

This engine oil provides maximum protection against corrosion, while the additives keep the engine free from internal contamination, sludge, and deposits. Moreover, Eurol Ultrance ST 5W-30 has fuel-saving properties and offers extended oil change intervals of up to 30,000 km.

Eurol Ultrance ST 5W-30 is recommended for applications where ACEA C2 with viscosity grade SAE 5W-30 is specified.

For further information, please consult the manual or look for oil recommendations on our online product selector at www.eurol.com.

Recommended for use

- ACEA C3
- Stellantis FPW9.55535/03
- PSA B71 2290
- GM dexos 2
- API SP

Physikalische Eigenschaften

i ilyomanoono Eigonoonanon		
Farbe	braun	
Dichte bei 20°C	0.852 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	70.2 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	12.1 cSt	ASTM D 445
Viskositätsindex	171	ASTM D 2270
Viskosität, dynamisch (CCS)	6174 cP	ASTM D 5293
Base number	10.7 mg	ASTM D 2896
Sulfatasche	0.8 wt%	ASTM D 874
Flammpunkt	230 °C	ASTM D 92
Stockpunt	-42 °C	ASTM D 97

Artikelnummer E100181 Version 1.0, 03-09-2024