



Motorcycle oils 4T - Fully Synthetic

# Eurol Harley Twinlube-FS 20W50

Fully synthetic motor oil for 4-stroke motorcycles

## Beschreibung

Eurol Harley Twinlube-FS 20W-50 is a fully synthetic engine oil without a friction modifier, especially developed for 4-stroke motorcycles.

Eurol Harley Twinlube-FS 20W-50 is based on fully synthetic base oils, giving optimized friction characteristics and offering excellent protection against wear, deposits, sludge and oxidation under all conditions. Aeration and foaming are avoided even under the roughest and toughest conditions.

Eurol Harley Twinlube-FS 20W-50 has a low volatility, reducing oil thickening and oil consumption to a bare minimum.

Due to the sophisticated formulation, this oil offers an excellent protection to gearboxes and wet disc clutches and prevents clutches from slipping and sticking.

Despite the high loads between the gears, the dedicated oil thickener hardly breaks down, so that even at high temperatures, the viscosity stays in grade to assure a strong lubricant film.

At low temperatures, Eurol Harley Twinlube-FS 20W-50 quickly builds up a tenacious lubricant film for an optimum protection at the cold start.

## Performance level

- API SJ
- JASO MA
- JASO MA2

## Physikalische Eigenschaften

Farbe	Bernsteinfarb	
Dichte bei 20°C	0.852 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	128.2 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	18.2 cSt	ASTM D 445
Viskositätsindex	159	ASTM D 2270
Viskosität, dynamisch (CCS)	2164 cP	ASTM D 5293
Flammpunkt	210 °C	ASTM D 93
Stockpunkt	-36 °C	ASTM D 97

Artikelnummer E100376  
Version 1.1, 07-12-2017

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.