



Motorcycle oils 4T - Mineral

Eurol Harley 20W-50

Minerales Motoröl für Harley Davidson Motorräder

Beschreibung

Eurol Harley Davidson oil has especially been developed for Harley Davidson motorcycles. This oil is formulated with selected base stocks and additives, reducing oil consumption to a minimum.

Eurol Harley Davidson oil has been applied for the lubrication of Harley Davidson motorcycles successfully, for many years.

Eurol Harley Davidson withstands heavy shock loads and offers good protection against corrosion and oxidation, so wear is reduced to a minimum. In short: a robust oil for a perfect lubrication which enables the Harley Davidson to last for years.

Performance level

- API SG
- JASO MA
- JASO MA2

Physikalische Eigenschaften

Farbe	braun	
Dichte bei 20°C	0.873 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	139.6 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	17.5 cSt	ASTM D 445
Viskositätsindex	138	ASTM D 2270
Viskosität, dynamisch (CCS)	4028 cP	ASTM D 5293
Base number	8.4 mg	ASTM D 2896
Sulfatasche	1.19 wt%	ASTM D 874
Flammpunkt	205 °C	ASTM D 93
Stockpunkt	-33 °C	ASTM D 97

Artikelnummer E100390
Version 4.1, 17-09-2020

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.