

### Heavy duty diesel engine oils - Semi-synthetic

# **Eurol Radiax 60**

Semi-synthetic engine oil for racing applications

## **Beschreibung**

Eurol® Radiax is an ultramodern synthetic motor oil, specially developed for race application. This product is applicable with methanol fuel.

Eurol® Radiax offers first-rate protection under the harshest circumstances by neutralising acidic combustion products, excellent wear protection of all vital parts. This oil has strong dispersing and deterging properties to prevent sludge and deposits.

A very high oil film strength even at high temperatures, combined with an excellent thermal and oxidative stability have resulted in several championships, especially in drag racing. Performance level • API CH-4

## Physikalische Eigenschaften

Farbe	braun	
Dichte bei 20°C	0.887 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	180.7 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	23.1 cSt	ASTM D 445
Viskositätsindex	156	ASTM D 2270
Viskosität, dynamisch (CCS)	239 cP	ASTM D 5293
Base number	11.7 mg	ASTM D 2896
Flammpunkt	239 °C	ASTM D 93
Stockpunt	-36 °C	ASTM D 97

Artikelnummer E100910 Version 2.0, 15-01-2021

#### Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturers instructions.