



Monograde engine oils - Mineral

## Eurol Super Premium SAE 30

Straight mineral motor oil

### Beschreibung

Eurol Super Premium SAE 30 is a straight mineral motor oil, especially developed for gasoline and diesel engines, operating under favourable working conditions.

Eurol Super Premium SAE 30 is blended from carefully selected solvent refined paraffinic base oils. The product has a low pour point, a high viscosity index and an excellent oxidation stability.

Eurol Super Premium SAE 30 can also be used in systems where there is not placed a load on the oil like in light duty gear boxes and circulation lubrication systems.

### Recommended for use

- API SA/CA

### Physikalische Eigenschaften

Farbe	Bernsteinfarb	
Dichte bei 20°C	0.875 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	103.6 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	11.5 cSt	ASTM D 445
Viskositätsindex	98	ASTM D 2270
Flammpunkt	260 °C	ASTM D 93
Stockpunkt	-27 °C	ASTM D 97

Artikelnummer E101170  
Version 1.2, 11-02-2022

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.