

Heavy duty diesel engine oils - Mineral

Eurol HDS 20W-20

Mineral motor oil for diesel engines

Beschreibung

Eurol HDS SF/CF 20W-20 has especially been developed for light and heavy duty gasoline and diesel engines and also stationary engines. This oil is also suitable for diesel engines operating on diesel fuel with a higher sulphur content (up to 0.5%).

Eurol HDS SF/CF 20W-20 has strong deterging and protecting capabilities. This assures the prevention of carbon deposits on pistons, valves and in the combustion chamber.

Eurol HDS SF/CF 20W-20 has strong anti-wear, anti-corrosion and antifoam characteristics and also a high oxidation stability to protect for oil thickening.

Eurol HDS SF/CF SAE 30, 40 and 50 both meet API CF-2 specification, which is especially required for Detroit Diesel engines.

Caution: Because of the presence of zinc-containing additive technology, this oil is NOT recommended for engines equipped with silver bearings/ components.

Performance level

- API CF-4
- API SF/CD
- API CF-2
- API CF
- ACEA E2
- MB 228.1
- MAN 271
- Deutz DQC I-02
- MIL-L-2104D

Recommended for use

- Ford WSS-M2C153-D
- MIL-L-46152C
- GM 6049-M
- GM 6048-M

Physikalische Eigenschaften

| i ilyontanoono Eigonoonatton | | |
|-----------------------------------|-----------|-------------|
| Farbe | braun | |
| Dichte bei 20°C | 0.87 kg/L | ASTM D 4052 |
| Viskosität, kinematisch bei 40°C | 62.1 cSt | ASTM D 445 |
| Viskosität, kinematisch bei 100°C | 8.6 cSt | ASTM D 445 |
| Viskositätsindex | 111 | ASTM D 2270 |
| Viskosität, dynamisch (CCS) | 2839 cP | ASTM D 5293 |
| Base number | 10.3 mg | ASTM D 2896 |
| Sulfatasche | 1.44 wt% | ASTM D 874 |
| Flammpunkt | 218 °C | ASTM D 93 |
| Stockpunt | -36 °C | ASTM D 97 |

Artikelnummer E101260 Version 3.0, 17-03-2020