



Tractor oils - S.T.O.U.

Eurol Altrack 10W-30 STOU

Universal, mineral tractor oil for engine and transmission

Beschreibung

Eurol Altrack 10W-30 STOU is a universal, multi-grade tractor oil (Super Tractor Oil Universal) and is especially developed for application in the engine, transmission and hydraulic system. The product provides a perfect cold start, reduces friction and keeps the engine clean.

Eurol Altrack 10W-30 STOU can be used all year round in tractors equipped with oil immersed disc brakes (so called 'wet brakes'). Because the oil can be applied in the engine, transmission, hydraulic system and wet brakes, it prevents mistakes in the oil selection and it reduces stock.

Eurol Altrack 10W-30 STOU allows an optimum drain interval for an economic use and maintenance. It provides an uncomplicated exchange of hydraulic equipment.

Eurol Altrack 10W-30 STOU offers a perfect protection against corrosion, oxidation and wear, even under extremely high loads, which occur in transmissions. Deterging and dispersing additives keep the oil and the system clean from pollution and impurities.

Performance level

- API CG-4/SF
- API GL-4
- ACEA E3
- Allison C-4
- MF M1135, MF M1139, MF M1143, MF M1144, MF M1145
- ZF TE ML 06B/06C/06R/07B
- Case MS 1206, MS1209
- MB 228.1
- MB 227.1
- MAN 271
- ZF TE-ML 07D
- MIL-L-2104D
- John Deere J21A
- Ford WSS-M2C159-B/C
- CNH MAT 3505
- CNH MAT 3525
- MIL-L-46152C
- Ford NH 82009201/2/3
- Ford WSS-M2C134-D
- John Deere J20C, J27
- NH 030 C, NH 024 C, NH 410 B, NH 420 A
- Caterpillar TO-2
- FNHA-2-C201

Recommended for use

- MIL-L-2105

Physikalische Eigenschaften

Farbe	braun	
Dichte bei 20°C	0.871 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	68.9 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	10.8 cSt	ASTM D 445
Viskositätsindex	146	ASTM D 2270
Viskosität, dynamisch (CCS)	5571 cP	ASTM D 5293
Flammpunkt	198 °C	ASTM D 93
Stockpunkt	-45 °C	ASTM D 97

Artikelnummer E105075
Version 4.0, 27-03-2023

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.