



Eurol Hykrol DAZ 32

Mineral hydraulic oil HVLP, with detergency, ashless, zinc-free

Beschreibung

Eurol Hykrol DAZ 32 is a hydraulic oil, formulated from high performance base stocks and specially selected additives. The product is ashless, zinc-free and has strong detergency properties.

Due to the emulsifying capabilities, Eurol Hykrol DAZ 32 is extremely suitable for hydraulic systems with a higher risk for water contamination (bridges, locks and on board ships). The emulsified water has no negative effects on the filterability and the corrosion protection.

Due to the high viscosity index, Eurol Hykrol DAZ 32 is suitable for heavily loaded hydraulic systems operating under strongly fluctuating temperatures.

Eurol Hykrol DAZ 32 can be used in systems with bronze or silver plated components. Because of the thermal and oxidation stability, the product will preserve its high quality, even under extreme loads.

NB: When changing from a zinc-based hydraulic or engine oil to Eurol Hykrol DAZ 32, the system should be flushed and cleaned prior to filling the system.

Performance level

- DIN 51524/2 (HLPD)
- Daimler DBL 6721

Physikalische Eigenschaften

Farbe	Bernsteinfarb	
Dichte bei 20°C	0.864 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	31 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	6.1 cSt	ASTM D 445
Viskositätsindex	152	ASTM D 2270
Flammpunkt	196 °C	ASTM D 93
Stockpunkt	-42 °C	ASTM D 97