



Eurol MTF 75W GL-4

Synthetic gear oil with fuel-saving properties

Beschreibung

Eurol MTF 75W GL4 is a synthetic gear oil, which can be used in final drives and manual transmissions.

Eurol MTF 75W GL4 is very well compatible with synchromesh and ensures very smooth shifting even at low temperatures.

Eurol MTF 75W GL4 contains special friction modifiers, which ensure sustainable fuel saving and less heat development.

Eurol MTF 75W GL4 ensures adequate lubrication at both very low, as very high temperatures and protects against corrosion, wear, thickening and deposits.

Eurol MTF 75W GL4 is compatible with most elastomers and seal materials and does not foam under extreme loads.

Performance level

- API GL-4
- MIL-L-2105

Recommended for use

- VW G 052 726
- VW G 052 512
- VW G 052 178
- VW G 052 171
- MB 235.73
- Ford WSS-M2C200-D2

Physikalische Eigenschaften

Farbe	Bernsteinfarben	
Dichte bei 20°C	0.846 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	37.4 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	6.7 cSt	ASTM D 445
Viskositätsindex	137	ASTM D 2270
Flammpunkt	180 °C	ASTM D 93
Stockpunkt	-42 °C	ASTM D 97

Artikelnummer E110073

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.