



Transmission oils - Semi-synthetic

Eurol MTF 75W-80 GL5

Synthetic transmission oil suitable for certain manual gearboxes

Beschreibung

Eurol MTF 75W-80 GL5 is a synthetic gear oil, which can be used in final drives and manual transmissions (where GL-5 quality is required).

Eurol MTF 75W-80 GL5 is very well compatible with synchromesh and ensures very smooth shifting even at low temperatures.

Eurol MTF 75W-80 GL5 has an excellent high load carrying capacity for an excellent absorption of sudden peak loads. The viscosity decrease due to heavy loads is only slightly, which will extend oil drain intervals (and in some cases lifetime filling) and ensures proper viscosity.

Eurol MTF 75W-80 GL5 contains special friction modifiers, which ensure sustainable fuel saving and less heat development.

Eurol MTF 75W-80 GL5 ensures adequate lubrication at both very low, as very high temperatures and protects against corrosion, wear, thickening and deposits.

Eurol MTF 75W-80 GL5 is compatible with most elastomers and seal materials and does not foam under extreme loads.

Performance level

- API GL-5
- MIL-L-2105 B/C/D

Recommended for use

- Fiat
- BMW 2300 7533 818
- Alfa Romeo
- LANCIA
- Volvo 97308
- VW 501 50
- BMW 2300 1434 404
- BMW 2300 7533 513
- BMW 83 22 0 309 031
- BMW 83 22 0 403 247
- BMW 83 22 7 533 818
- GM/Opel 19 40 182
- GM/Opel 19 40 757
- GM/Opel 19 40 768GM/Opel 19 40 776
- Ford WSS-M2C200-C/C2/C3
- Citroen
- Peugeot
- Renault

Physikalische Eigenschaften

Farbe	Gelb	
Dichte bei 20°C	0.882 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	49.8 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	9.4 cSt	ASTM D 445
Flammpunkt	190 °C	ASTM D 93
Stockpunt	-48 °C	ASTM D 97

Artikelnummer E110080 Version 1.0, 04-03-2016