



Transmission oils - Mineral

## Eurol Eurolube SAE 80W GL1

Mineral transmission oil for light duty gears with straight- and bevel teeth

### Beschreibung

Eurolube is blended with solvent refined paraffinic base stocks and anti-wear additives. The product is recommended for light duty gearboxes with straight or bevel teeth.

Eurolube has a high viscosity index and a low pour point which guarantees a constant safe operating condition, both at low starting temperatures as well as at high full load temperatures.

Seals are not affected by Eurolube. The product has an excellent thermal and oxidation stability, ensuring a long durability. Parts are protected from rust and corrosion.

### Recommended for use

- API GL-1

### Physikalische Eigenschaften

| Farbe                             | Bernsteinfarb |             |
|-----------------------------------|---------------|-------------|
| Dichte bei 20°C                   | 0.867 kg/L    | ASTM D 4052 |
| Viskosität, kinematisch bei 40°C  | 65.8 cSt      | ASTM D 445  |
| Viskosität, kinematisch bei 100°C | 8.7 cSt       | ASTM D 445  |
| Viskositätsindex                  | 104           | ASTM D 2270 |
| Flammpunkt                        | 238 °C        | ASTM D 93   |
| Stockpunkt                        | -27 °C        | ASTM D 97   |

Artikelnummer E110500  
Version 1.3, 11-02-2022

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.