



Eurol HPG 80W-90 GL5

Mineral gear oil for hypoid gears and hub reductions

Beschreibung

Eurol HPG Gear Oil is a mineral gear oil, formulated according to the latest phosphor - sulphur technology. This special additive technology assures an excellent protection against metal-to-metal contact of the gears under the most severe operating conditions, even under shock loads.

Eurol HPG Gear Oil contains special additives, leaving a protecting oil film for optimum corrosion protection. Furthermore, the SAE 80W and 85W-140 viscosity grades have an excellent low temperature fluidity for an optimum performance during all seasons.

Eurol HPG Gear Oil shows an excellent oxidation and thermal stability. Seals are not affected by this product.

Eurol HPG Gear Oil is recommended for use in hypoid gears, hub reductions, gearboxes, PTO's and differentials where an API GL-5, MIL-L 2105-D and Mack GO-G are recommended. The SAE 85W-90 viscosity grade can also be applied where MB 235.0 is prescribed.

Performance level

- API GL-5
- MIL-L-2105 B/C/D

Recommended for use

Mack GO-G

Physikalische Eigenschaften

Farbe	braun	
Dichte bei 20°C	0.883 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	136.9 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	14.1 cSt	ASTM D 445
Viskositätsindex	100	ASTM D 2270
Flammpunkt	244 °C	ASTM D 93
Stockpunt	-33 °C	ASTM D 97

Artikelnummer E110630 Version 1.3, 18-09-2020

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.