



Transmission oils - Mineral

Eurol HPG EP SAE 85W-90 GL5

Mineral gear oil for hypoid gears and hub reductions

Beschreibung

Eurol HPG 85W-90 is a mineral gear oil, formulated according to the latest phosphor - sulphur technology. This special additive technology assures an excellent protection against metal-to-metal contact of the gears under the most severe operating conditions, even under shock loads.

Eurol HPG 85W-90 contains special additives, leaving a protecting oil film for optimum corrosion protection.

Eurol HPG 85W-90 shows an excellent oxidation and thermal stability. Seals are not affected by this product.

Eurol HPG 85W-90 is recommended for use in hypoid gears, hub reductions, gearboxes, PTO's and differentials where an API GL-5 , MIL-L 2105-D and Mack GO-G are recommended. The Eurol HPG 85W-90 can also be applied where MB 235.0 is prescribed.

Performance level

- API GL-5
- MIL-L-2105 B/C/D

Recommended for use

Mack GO-G

Physikalische Eigenschaften

Farbe	braun	
Dichte bei 20°C	0.883 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	136.9 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	14.1 cSt	ASTM D 445
Viskositätsindex	100	ASTM D 2270
Flammpunkt	244 °C	ASTM D 93
Stockpunt	-30 °C	ASTM D 97

Artikelnummer E110635 Version 1.4, 23-01-2023