



Gearbox oils - ATF+CVT

## Eurol Transfluid ATF-CVT

Fully synthetic multifunctional transmission oil for both automatic and continuously variable transmissions

### Beschreibung

Eurol Transfluid ATF-CVT is a fully synthetic multifunctional oil that is suitable for both automatic transmissions and continuously variable transmissions for vehicles produced in North and South America, Europe and Asia.

Eurol Transfluid ATF-CVT ensures that automatic and continuously variable transmissions continue to shift easily under difficult conditions, because the product prevents unnecessary friction. The low pour point and the high VI ensure that Eurol Transfluid ATF-CVT can be used in a wide temperature range.

The combination of high-quality base oils in combination with a 'state-of-the-art' additive that can be used for both ATF and CVT applications provides a very extensive list of applications in which Eurol Transfluid ATF-CVT can be used .

Eurol Transfluid ATF-CVT produces excellent properties and easily meets the most important drain intervals due to its very good oxidation and thermal stability.

Cause Eurol Transfluid ATF-CVT is suitable for both automatic and continuously variable transmissions, it has a very wide range of applications and an extensive 'suitable for use' list with specifications for which it can be used.

### Recommended for use

- Aisin Warner AW-1
- VW G 052 055
- VW G 052 180
- VW G 052 516
- VW G 055 025
- Mercon SP
- Mercon V
- GM Dexron III
- ATF-Z1, Honda
- Honda/Kia/Mitsubishi SP-III
- Mitsubishi SP-IV
- ATF RED 1K
- Hyundai/KIA CVT-1
- JWS 3309/3314/3317
- JWS 3320 (CVT)
- MB 236.1 - 236.11
- MB 236.20
- Nissan Matic C, D, J, K, P, S
- Nissan NS-1
- Nissan NS-2
- Nissan NS-3
- Nissan ePower
- Toyota CVT FE
- Volvo 97335
- Volvo 97325
- ZF Lifeguardfluid 5, 6, 8
- For more specifications, check our website eurol.com

### Physikalische Eigenschaften

Farbe	braun	
Dichte bei 20°C	0.843 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	34.2 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	7.2 cSt	ASTM D 445
Viskositätsindex	180	ASTM D 2270
Flammpunkt	213 °C	ASTM D 93
Stockpunkt	-45 °C	ASTM D 97

Artikelnummer E113668  
Version 1.5, 07-02-2024

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.