



Eurol Syncool B 3145

Versatile water miscible metalworking fluid

Beschreibung

Eurol Syncool B 3145 is a mineral, emulsifiable cutting fluid for general cutting operations, with a wide range of applications. After mixing with water, a stable white milky emulsion will be formed.

Eurol Syncool B 3145 does not contain boric acid or formaldehyde donors and is suitable for turning, drilling and sawing operations of various types of steel as well as aluminium. The product protects tools and work pieces against corrosion and has a low foaming tendency.

Add Eurol Syncool B 3145 to water with 10° dH up to 30° dH while stirring. Never add Eurol Syncool B 3145 first and water second, as it will not form a stable emulsion.

Eurol Syncool B 3145 is extremely suitable for cutting, turning, milling, drilling and sawing.

Eurol Syncool B 3145 gives 1° Brix per % in emulsion, at a recommendend use concentration of 6% in water for general machining and 8% for medium to heavy duty machining.

Physikalische Eigenschaften

Farbe	Gelb	
Dichte bei 20°C	0.955 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	70.6 cSt	ASTM D 445
Flammpunkt	100 °C	ASTM D 93
pH-Wert	9.7	

Artikelnummer E120710
Version 1.0, 18-06-2019

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.