



Industrial oils - Slideway oil

Eurol Slideway Oil 68

High performance lubricant for metal and plastic slideways

Beschreibung

Eurol Slideway Oil 68 is a series of new zinc free high performance oils, recommended for the lubrication of both metal, as well as plastic slideways.

Eurol Slideway Oil 68 provides excellent friction characteristics and lubricity, eliminating 'stick-slip'. Because of this, a very good surface finish can be achieved, with less production rejects.

Eurol Slideway Oil 68 has excellent demulsifying properties and will not drip, which extends the lifetime of both the slideway oil, as well as the cutting fluid. Oxidation and corrosion inhibitors keep the oil and the machine tool in a perfect condition.

Besides an excellent protection against corrosion, Eurol Slideway Oil 68 also offers a strong and stable lubricant film.

Eurol Slideway Oil 68 can also be used in hydraulic systems, as a chain oil in circulating lubrication systems and for the lubrication of conveyor belts.

Performance level

- DIN 51524/2 (HLP)
- Cincinnati Machine P-47
- GM LS-2
- DIN 51 502 CGLP

Physikalische Eigenschaften

Farbe E	Bernsteinfarben	
Dichte bei 20°C	0.865 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	67.7 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	9.4 cSt	ASTM D 445
Viskositätsindex	117	ASTM D 2270
Flammpunkt	184 °C	ASTM D 93
Stockpunt	-9 °C	ASTM D 97

Artikelnummer E121490 Version 2.1, 08-08-2023