



Industrial oils - Vacuum pump

Eurol Vacuumolie ISO-VG 68

Mineral vacuum pump oil

Beschreibung

Eurol Vacuum pump Oil ISO-VG 68 is an oil with a very good oxidation stability. Therefore, this oil is perfectly suitable for application in vacuum pumps, operating under heavy duty working conditions.

Eurol Vacuum pump Oil ISO-VG 68 is blended from solvent refined paraffinic base oils with low vapour pressure. A minimum amount of additives provides sufficient protection against wear, rust and corrosion, while water and vapour are rapidly separated.

Eurol Vacuum pump Oil ISO-VG 68 has a naturally high viscosity index, which prevents inconvenient viscosity changes, caused by temperature differences.

Performance level

- DIN 51524/2 (HLP)
- U.S. Steel 127
- U.S. Steel 126
- Sperry Vickers I-286-S
- AFNOR NF E 48-603 HM
- AFNOR NF E 48-603 HL
- DIN 51524/1 (HL)

Physikalische Eigenschaften

Farbe	Bernsteinfarb	
Dichte bei 20°C	0.867 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	65.8 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	8.7 cSt	ASTM D 445
Viskositätsindex	104	ASTM D 2270
Flammpunkt	238 °C	ASTM D 93
Stockpunkt	-27 °C	ASTM D 97

Artikelnummer E122566
Version 1.3, 11-02-2022

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.