



Eurol Vacuumolie ISO-VG 220

Mineral vacuum pump oil

Beschreibung

Eurol Vacuum pump Oil ISO-VG 220 is an oil with a very good oxidation stability. Therefore, this oil is perfectly suitable for application in vacuum pumps, operating under heavy duty working conditions.

Eurol Vacuum pump Oil ISO-VG 220 is blended from solvent refined paraffinic base oils with low vapour pressure. A minimum amount of additives provides sufficient protection against wear, rust and corrosion, while water and vapour are rapidly separated.

Eurol Vacuum pump Oil ISO-VG 220 has a naturally high viscosity index, which prevents inconvenient viscosity changes, caused by temperature differences.

Performance level

- DIN 51517/3 (CLP)
- AISE (US Steel) 224
- AGMA 9005/E02
- ISO 12925-1 CKD

Physikalische Eigenschaften

Farbe	braun	
Dichte bei 20°C	0.887 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	210 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	18 cSt	ASTM D 445
Viskositätsindex	95	ASTM D 2270
Flammpunkt	250 °C	ASTM D 93
Stockpunkt	-27 °C	ASTM D 97

Artikelnummer E122574
Version 2.0, 31-05-2022

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.