



Industrial oils - Rust preventives

Eurol Cablelube 88

Synthetic lubricant protecting cables from wear and corrosion

Beschreibung

Eurol Cablelube 88 is a synthetic cable lubricant, especially developed to penetrate deeply into the cable, hereby ensuring a complete protection.

Eurol Cablelube 88 contains a solvent which ensures that the product can be applied easily. The solvent evaporates to leave behind a protective layer between the separate strands of the cable.

Eurol Cablelube 88 offers rust- and corrosion protective properties to the cable in damp circumstances.

Physikalische Eigenschaften

| Farbe | Farblos | |
|-----------------------------------|------------|-------------|
| Dichte bei 20°C | 0.845 kg/L | ASTM D 4052 |
| Viskosität, kinematisch bei 40°C | 29.9 cSt | ASTM D 445 |
| Viskosität, kinematisch bei 100°C | 6.7 cSt | ASTM D 445 |
| Viskositätsindex | 192 | ASTM D 2270 |
| Flammpunkt | 104 °C | ASTM D 93 |
| Stockpunt | -18 °C | ASTM D 97 |

Artikelnummer E123475
Version 1.0, 04-03-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.