



## Eurol Cirturo ISO-VG 46

Ashless mineral turbine and circulation oil / R&O oil

### Beschreibung

Eurol Cirturo ISO-VG 46 is an ashless, high-quality turbine and circulation oil / R&O oil, which can be used for turbine lubrication, lubrication for gears and circulating systems, low loads hydraulic systems and guide- and roller bearings.

Eurol Cirturo ISO-VG 46 distinguishes itself by excellent rust and corrosion properties and also by a robust oxidation stability. Water is separated very fast and effectively, foam formation will be prevented, resulting in optimal lubricating properties.

### Performance level

- Cincinnati-Machine P-55
- Westinghouse Electric Corp. Turbine Oil Spec
- ISO L-DAA, DAB, DAH, DAG
- DIN 51506: VBL/VCL/VDL
- CEGB Standard 207001
- Alstom HTGD 90 117 V0001 S
- AFNOR NF E 48-603 HL
- DIN 51524/1 (HL)
- DIN 51517/2 (CL)
- MIL-L-17672 D
- Siemens TLV 9013 04
- U.S. Steel 120
- Brown Boveri HTGD 90117
- BS 489
- G.E. GEK 32568 A/C
- ISO 8068

### Physikalische Eigenschaften

Farbe	Bernsteinfarb	
Dichte bei 20°C	0.856 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	45 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	7.1 cSt	ASTM D 445
Viskositätsindex	116	ASTM D 2270
Flammpunkt	249 °C	ASTM D 93
Stockpunkt	-33 °C	ASTM D 97

Artikelnummer E123861  
Version 1.1, 23-09-2021

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.