



Technical fluids - Mineral

Eurol Bicycle Oil

Lubricant for bicycles

Beschreibung

Performance level

- DIN 51524/2 (HLP)
- U.S. Steel 127
- U.S. Steel 126
- Sperry Vickers I-286-S
- AFNOR NF E 48-603 HM
- AFNOR NF E 48-603 HL
- DIN 51524/1 (HL)

Physikalische Eigenschaften

| Farbe | Bernsteinfarb | | |
|-----------------------------------|---------------|-------------|--|
| Dichte bei 20°C | 0.848 kg/L | ASTM D 4052 | |
| Viskosität, kinematisch bei 40°C | 32.4 cSt | ASTM D 445 | |
| Viskosität, kinematisch bei 100°C | 5.8 cSt | ASTM D 445 | |
| Viskositätsindex | 120 | ASTM D 2270 | |
| Flammpunkt | 227 °C | ASTM D 93 | |
| Stockpunt | -36 °C | ASTM D 97 | |

Artikelnummer E127250
Version 3.1, 11-02-2022

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.