



Coolants & screenwash

Eurol Coolant -26°C VCS-2

Longlife coolant for Renault and Volvo Trucks

Beschreibung

Eurol Coolant -26°C VCS-2 is a long-life coolant, specifically developed for Volvo and Renault trucks. This coolant provides reliable protection for the cooling system and optimal heat transfer, even under extreme conditions. Thanks to Organic Acid Technology (OAT), the coolant is compatible with other OAT-based coolants and meets the requirements of modern diesel engines.

Eurol Coolant -26°C VCS-2 is suitable for engines made of cast iron, aluminum, or a combination of these materials. It offers excellent corrosion protection, essential for cooling systems with aluminum and copper alloys. This coolant is particularly suited for high-performance engines where the protection of aluminum at high temperatures is crucial. Furthermore, it is compatible with Battery Electric Vehicles (BEVs), including both passenger cars and heavy-duty vehicles.

Benefits:

- Provides protection against freezing down to -26°C.
- Suitable for both BEVs and diesel engines.
- Protects engines for up to 4 years or 500,000 km.
- Safe for rubbers, plastics, and metals.
- Excellent corrosion protection for aluminum and copper alloys.

Eurol Coolant -26°C VCS-2 is ready for immediate use and delivers reliable performance under the most demanding conditions. Its long service life helps reduce maintenance costs by providing continuous protection against wear and corrosion.

Consult the manual for more information or use our product advisor at www.eurol.com for advice on the right coolant for your vehicle.

Performance level

- Volvo VCS-2
- Renault RTCS-2
- STJLR.03.5212
- ASTM D3306
- ASTM D6210

Recommended for use

- CNH MAT 3624
- CNH MAT 3724
- DTFR 29D110 (MB 326.3)
- Deutz DQC CB-14
- Fiat 9.55523
- Ford WSS-M97B44-D
- GCM34
- GMW 18270
- GMW 3420
- Komatsu 07.892

Physikalische Eigenschaften

Farbe	Orange	
Dichte bei 20°C	1.057 kg/L	ASTM D 4052
Flammpunkt	111 °C	ASTM D 93
Frostschutz	-26 °C	ASTM D 1177

Artikelnummer E504143
Version 1.0, 19-09-2024

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.