



Technical fluids - Aerosols

# Eurol Zinc Protect Spray 400ML

Qualitatively high-end galvanizing spray

## Beschreibung

Eurol Zinc spray is a high-quality spray with sprayable zinc compound (Zinc 98%).

Eurol Zinc spray has a galvanizing function which superbly protects untreated iron and steel against corrosion. Through its cathodic function, Eurol Zinc spray is very frugal, yet highly efficient.

Eurol Zinc spray offers a good resistance against mechanical shocks, abrasions and erosion.

Eurol Zinc spray should be applied on a clean, dry and greasfree surface. Paint remnants and rust need to be removed before application. Eurol ZinCspray is after hardening paintable.

Eurol Zinc spray needs to be shaken vigorously for 30 seconds before applying and should be sprayed at 20cm from the galvanizing target.

2 Layers of Eurol Zinc spray need always be applied at a two-hour interval.

Eurol Zinc spray keeps for 3 years in an unopened can, when stored in a cool and dry place at temperatures between +5°C en +25°C.

## Physikalische Eigenschaften

Farbe	Farblos
Flammpunkt	-80 °C    ASTM D 93

Artikelnummer E701140  
Version 1.0, 16-02-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.