



Technical fluids - Aerosols

Eurol PTFE Super Lube Spray 400ML

Lubricant with PTFE

Beschreibung

Eurol PTFE Spray is high quality lubricant based on PTFE and is proper for the lubrication of metal and plastic parts. The product nebulizes as a lubricant with penetration properties and solidifies at a later stage as a grease.

Eurol PTFE Spray is specially developed for the lubrication of parts that are long-term exposed to high load. The PTFE offers a long-term protection against friction and prevents wear.

Eurol PTFE Spray can be used in many applications where contact between plastics/rubbers with metal needs to be lubricated. Applications such as machines, pulleys, chains, derailleurs, roller bearings and conveyors.

Eurol PTFE Spray must be shaken well before use. The to be treated object must be cleaned, degreased and dried before use. Spray at approx. 20-25 cm from the object. To achieve best results, Eurol PTFE Spray should be applied when the to be treated objects are in motion, if possible.

Use Eurol PTFE Spray only in well ventilated areas. In case of eye contact immediately rinse eyes with plenty of water.

Eurol PTFE Spray has a shelf life of 3 years in an unopened container in a cool and dry place with a temperature range between +5°C and +25°C.

Physikalische Eigenschaften

Farbe	Gelb
-------	------

Artikelnummer E701460
Version 1.1, 18-06-2019

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.