



# Eurol Motorcycle Fuel Treat

Fuel additive for conserving petrol fuel

## Beschreibung

Eurol Motorcycle Fuel Treat is developed to protect your petrol powered machine against gum, varnish, rust and corrosion throughout the fuel system.

Petrol consists of a complex mixture of hydrocarbons which is very sensitive to light and air. Petrol without any antioxidant is prone to oxidation and gum formation. Stagnant petrol only keeps for approximately 3 months when it is left unprotected, all the while lowering the octane number (RON).

Oxygen negatively affects gasoline, changing the molecular structure in such a way that the octane number is lowered. Eurol Motorcycle Fuel Treat can prevent deterioration of petrol during seasonal or longer storage by improving oxidative stability.

Petrol containing ethanol (E10) is especially subject to absorbing atmospheric moisture, then forming gums or solids. When that water mixture gets into a carburetor and rubberized parts, corrosion becomes a real problem.

The 100ml bottle of Eurol Motorcycle Fuel Treat is recommended for use in 15L to 25L of fuel. Allow the Eurol Motorcycle Fuel Treat to run through the fuel system for up to a few minutes to ensure a proper treatment and not just the fuel stored in the fuel tank. Add the Eurol Motorcycle Fuel Treat to the fuel tank before refueling. For best results, use when your fuel is likely to sit for more than one month.

Users should consult the Material Safety Data Sheet of Eurol Motorcycle Fuel Treat for information about storage and shelf life. Please ask Eurol Research & Development if any further information is required.

## Physikalische Eigenschaften

Farbe	Gelb	
Dichte bei 20°C	0.804 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	2.8 cSt	ASTM D 445
Flammpunkt	62 °C	ASTM D 93

Artikelnummer E802810  
Version 1.0, 25-03-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.