



Greases

## Eurol White Lithium Grease EP2

White multi-purpose grease with EP additives

### Beschreibung

Eurol White Grease EP 2 has been especially developed for the lubrication of ball and roller bearings, working under conditions requiring EP additives.

Eurol White Grease EP 2 shows excellent oxidation stability and anti-wear properties.

Eurol White Grease EP 2 is water-repellent and offers good corrosion protection. Therefore, it is often used for sealing filters, chains and filter housings of cross motorcycles.

Because of the colour, Eurol White Grease EP 2 is pleasant to use. It prevents dirt of the object to be lubricated on to skin or clothing.

### Performance level

- DIN 51825: K2K-30
- ISO-L-XCCEA2

### Physikalische Eigenschaften

Farbe	Weiß	
Dichte bei 20°C	0.94 kg/L	ASTM D 4052
NLGI Konsistenzklasse	2	
Verdickertyp	Lithium	
Base oil type	Mineral	
Grundöl Viskosität	110 cSt	ASTM D 445
4-ball weld load	200 kg	ASTM D 2596
Temperaturbereich	-30 – 120 °C	
Dropping point	180 °C	

Artikelnummer E901080  
Version 1.0, 16-02-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.