



Greases

Eurol Calieur Grease EP 2

Lubricating grease with water repellent properties

Beschreibung

Eurol Calieur Grease EP 2 is formulated from a high viscosity base oil and a calcium-lithium thickener. Besides high performance Extreme Pressure additives, it also contains anti-corrosion and anti-wear inhibitors.

Eurol Calieur Grease EP 2 is highly water repellent and has excellent sealing properties against mud and dirt. Moreover, the product is strongly adhering, which ensures perfect lubrication under all circumstances.

Eurol Calieur Grease EP 2 is extremely suitable for high temperature conditions. Due to the long life-time of this grease, it enables extended re-lubrication intervals. Because of the high viscosity base oil, this product is not recommended for high speed bearings.

Performance level

- DIN 51825: KP2K-20
- ISO-L-XBCIB2

Physikalische Eigenschaften

Farbe	braun	
Dichte bei 20°C	1 kg/L	ASTM D 4052
Flammpunkt	150 °C	ASTM D 93
NLGI Konsistenzklasse	2	ASTM D 217
Verdickertyp	Calcium Lithium	
Base oil type	Mineral	
Grundöl Viskosität	1100 cSt	ASTM D 445
4-ball weld load	550 kg	ASTM D 2596
Temperaturbereich	-20 – 120 °C	
Dropping point	180 °C	IP 396

Artikelnummer E901320
Version 1.1, 04-12-2023

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.