



Greases

Eurol Prop-Shaft Grease EP 2

Multi-Purpose grease for ball - and roller bearings

Beschreibung

Eurol Prop-Shaft Grease EP 2 and EP 3 have been developed for the lubrication of rotation points under normal load conditions and wet environments like sterntubes of outboard motors.

Eurol Prop-Shaft Grease EP 2 and EP 3 can also be applied for ball bearings, provided that temperatures and loads do not increase too much. Due to the structure, the product is also suitable for the lubrication of water pumps and cables.

Eurol Prop-Shaft Grease EP 2 and EP 3 are formulated from a lithium-soap thickener, naphthenic base oils and polymers. The product has a natural resistance against water, offers a good resistance against ageing and withstands temperatures up to 70°C.

Performance level

- DIN 51825: KP2K-30
- ISO-L-XCCIB 2

Physikalische Eigenschaften

| | | |
|-----------------------|--------------|-------------|
| Farbe | Gelb-braun | |
| Dichte bei 20°C | 0.94 kg/L | ASTM D 4052 |
| NLGI Konsistenzklasse | 2 | |
| Verdickertyp | Lithium | |
| Base oil type | Mineral | |
| Grundöl Viskosität | 110 cSt | ASTM D 445 |
| 4-ball weld load | 260 kg | ASTM D 2596 |
| Temperaturbereich | -30 – 120 °C | |
| Dropping point | 190 °C | |

Artikelnummer E901470
Version 1.0, 25-03-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.