



Greases

Eurol Prop-Shaft grease EP 3

Multi-Purpose grease for ball- and roller bearings

Beschreibung

Eurol Prop-Shaft Grease EP 3 has been developed for the lubrication of rotation points under normal load conditions and wet environments like sterntubes of outboard motors.

Eurol Prop-Shaft Grease EP 3 can also be applied for ball bearings, provided that temperatures and loads do not increase too much. Due to the structure, the product is also suitable for the lubrication of water pumps and cables.

Eurol Prop-Shaft Grease EP 3 is formulated from a lithium-soap thickener, naphthenic base oils and polymers. The product has a natural resistance against water, offers a good resistance against ageing and withstands temperatures up to 70°C.

Performance level

- DIN 51825: KP3K-20
- ISO 6743 ISO-L-XBCEB3

Physikalische Eigenschaften

Farbe	Hellbraun	
Dichte bei 20°C	0.9 kg/L	ASTM D 4052
NLGI Konsistenzklasse	3	
Verdickertyp	Lithium	
Base oil type	Mineral	
Grundöl Viskosität	120 cSt	ASTM D 445
4-ball weld load	240 kg	ASTM D 2596
Temperaturbereich	-30 – 120 °C	
Dropping point	180 °C	

Artikelnummer E901472
Version 1.0, 25-03-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.