



Eurol Hykrol FG ISO-VG 46

Hydraulic oil for application in the food industry

Beschreibung

Eurol Hykrol FG ISO-VG 46 is an especially developed, non-toxic, synthetic lubricant for industrial applications in the food industry. It can be used for hydraulic systems, as an airline fluid and in light loaded high speed gearboxes.

Eurol Hykrol FG ISO-VG 46 is applied in the food processing industry like: poultry, meat, bakeries, breweries, dairy and pet-food industry.

Eurol Hykrol FG ISO-VG 46 offers excellent protection against oxidation, rust, corrosion and foam building. The product has good anti-wear properties.

Eurol Hykrol FG ISO-VG 46 is fully compatible with gaskets and seals and can be mixed with mineral oils. Water will be immediately demulsified from the oil.

Performance level

- DIN 51517/3 (CLP)
- DIN 51524/3 (HVLP)
- DIN 51506: VDL
- NSF H1

Physikalische Eigenschaften

Farbe	Farblos bis	
Dichte bei 20°C	0.828 kg/L	ASTM D 4052
Viskosität, kinematisch bei 40°C	46.5 cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	8.2 cSt	ASTM D 445
Viskositätsindex	151	ASTM D 2270
Flammpunkt	199 °C	ASTM D 93
Stockpunkt	-61 °C	ASTM D 97

Artikelnummer E902697
Version 2.0, 17-05-2021

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.