



Passenger car engine oils - Fully Synthetic

Eurol Elance 5W-30

Fully synthetic fuel economy engine oil, ACEA C3/C2 and Renault RN17

Description

Eurol Elance 5W-30 is a fully synthetic high performance engine oil for gasoline and diesel vehicles.

Eurol Elance 5W-30 provides an extremely stable lubricant film at the cold start and offers high thermal stability under severe driving operating conditions (motorway and urban traffic). The oil is able to flow and to lubricate critical parts, preventing wear and ensuring engine protection.

Eurol Elance 5W-30 provides maximum protection against rust and corrosion, while the used additive package keeps the engine clean and well lubricated.

Eurol Elance 5W-30 has low sulphated ash contents and also low levels of phosphor and sulphur (so called "mid-SAPS" technology).

Eurol Elance 5W-30 is suitable for use in applications where Renault RN17 is prescribes as well as applications where RN0700 and RN0710 are prescribed.

Approved

API SN

Performance level

- ACEA C2
- ACEA C3
- VW 505.01
- MB 229.51
- MB 229.52 • MB 229.31
- BMW Longlife-04 • GM dexos 2
- VW 505.00
- OV 040 1547 D30

Recommended for use

- Renault RN0700 / 0710
- Renault RN17
- Dexos D

Physical properties

i ilyolodi proportioo		
Colour	brown	
Density at 20°C	0.851 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	73.2 cSt	ASTM D 445
Viscosity, kinematic at 100°C	12.1 cSt	ASTM D 445
Viscosity Index	163	ASTM D 2270
Viscosity, dynamic (CCS)	5832 cP	ASTM D 5293
Base number	8.0 mg	ASTM D 2896
Sulphated ash	0.78 wt%	ASTM D 874
Flash point	200 °C	ASTM D 93
Pour point	-36 °C	ASTM D 97

Article number E100012 Version 9.0, 15-09-2022