



Passenger car engine oils - Fully Synthetic

Eurol Elance 5W-30

Fully synthetic fuel economy engine oil, ACEA C3/C2

Description

Eurol Elance 5W-30 is a fully synthetic high performance engine oil for gasoline and diesel vehicles.

Eurol Elance 5W-30 provides an extremely stable lubricant film at the cold start and offers high thermal stability under severe driving operating conditions (motorway and urban traffic). The oil is able to flow and to lubricate critical parts, preventing wear and ensuring engine protection.

Eurol Elance 5W-30 provides maximum protection against rust and corrosion, while the used additive package keeps the engine clean and well lubricated.

Eurol Elance 5W-30 has low sulphated ash contents and also low levels of phosphor and sulphur (so called "mid-SAPS" technology).

Eurol Elance 5W-30 is suitable for use in applications where Renault RN17 is prescribed as well as applications where RN0700 and RN0710 are prescribed. Eurol Elance 5W-30 is also suitable for use in Hyundai, Kia, Toyota, Honda, Subaru, Nissan engines where ACEA C2 or C3 is recommended.

Performance level

- API SP
- API SN
- ACEA C2
- ACEA C3
- VW 505.01
- MB 229.51
- MB 229.52
- MB 229.31
- BMW Longlife-04
- OV 040 1547 - G30
- OV 040 1547 - D30

Recommended for use

- API CF
- VW 505.00
- GM dexos 2
- GM-LL-A-025
- GM-LL-B-025
- Fiat 9.55535-S3
- Fiat 9.55535-S1
- Renault RN0700 / 0710
- Renault RN17
- Dexos D

Physical properties

Colour	brown	
Density at 20°C	0.851 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	73.2 cSt	ASTM D 445
Viscosity, kinematic at 100°C	12.1 cSt	ASTM D 445
Viscosity Index	163	ASTM D 2270
Viscosity, dynamic (CCS)	5832 cP	ASTM D 5293
Base number	8.0 mg	ASTM D 2896
Sulphated ash	0.78 wt%	ASTM D 874
Flash point	229 °C	ASTM D 92
Pour point	-36 °C	ASTM D 97

Article number E100012
Version 9.0, 15-09-2022

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.