



Passenger car engine oils - Fully Synthetic

Eurol Ultrance FDE 0W-30

Fully synthetic mid-SAPS motor oil for gasoline and diesel engines

Description

Eurol Ultrance FDE 0W-30 is a fully synthetic ultra high performance oil for gasoline and diesel engines in passenger cars, especially for the most recent Ford diesel engines. Eurol Ultrance FDE 0W-30 fulfills the requirements of Ford WSS-M2C950-A.

Eurol Ultrance FDE 0W-30 quickly provides an extremely stable lubricant film at the cold start and offers high thermal stability under heavy duty operating conditions.

Eurol Ultrance FDE 0W-30 offers optimum dispersancy and detergency, keeping the engine clean.

Eurol Ultrance FDE 0W-30 provides maximum protection against rust and corrosion, while special additives keep all parts free from dirt, sludge and deposits.

Eurol Ultrance FDE 0W-30 is also recommended for vehicles for which an engine oil meeting ACEA C2 (2012) with the viscosity grade 0W-30 is prescribed.

Approved

• STJLR.03.5007

Performance level

- API SP
- ACEA C2
- Ford WSS M2C-950A
- VWC 53035

Physical properties

Colour	brown	
Density at 20°C	0.839 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	47.7 cSt	ASTM D 445
Viscosity, kinematic at 100°C	9.8 cSt	ASTM D 445
Viscosity Index	197	ASTM D 2270
Viscosity, dynamic (CCS)	5313 cP	ASTM D 5293
Base number	8.0 mg	ASTM D 2896
Flash point	232 °C	ASTM D 93
Pour point	-51 °C	ASTM D 97

Article number E100025 Version 4.0, 26-04-2024