



POWERING  
PERFORMANCE

# Eurol SHPD 15W-40 MF

## Mineral motor oil for mixed fleet

Article number E100027 Version 3.0 14/04/2025

### Product information

Eurol SHPD 15W-40 MF is an engine oil suitable for heavily loaded commercial vehicles. The product can also be used in gasoline, LPG, and lightly loaded diesel engines, with or without turbo and/or with a catalyst and/or common rail system.

Eurol SHPD 15W-40 MF meets a large number of leading OEM specifications and is therefore an ideal multifunctional engine oil for a mixed fleet.

Eurol SHPD 15W-40 MF fully complies with the strict standards regarding combustion residues on the piston crown, in the top piston ring, and on the rest of the piston. Due to its stability against high temperatures and aging, as well as the use of strong detergent additives, Eurol SHPD 15W-40 MF ensures that the oil and the engine remain in good condition.

Wear is minimized, even under the toughest operating conditions, ensuring the quality of Eurol SHPD 15W-40 MF throughout the entire oil change interval, regardless of the engine type.

The base oils of Eurol SHPD 15W-40 MF not only provide a trouble-free cold start but also fuel savings and reduced oil consumption due to less oil evaporation.

#### Approved

- Mack EO-N
- Renault VI RLD-2
- Volvo VDS-3

#### Performance level

- ACEA A3/B4
- ACEA E7
- Allison C-4
- API SL/CI-4
- Caterpillar ECF-1-A
- Caterpillar ECF-2
- CES 20076
- CES 20077
- CES 20078
- DDC Oil Category 2
- Detroit Diesel DDC 93K215
- Deutz DQC III-10
- DTFR 15B110 (MB 228.3)
- Global DHD-1
- JASO DH-1
- Mack EO-M Plus
- MAN M 3275
- MB 229.1
- MTU type 2
- Renault RLD
- Voith Class A

**Eurol B.V., Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 88 250 22 00, info@eurol.com, eurol.com**

This document is intended to inform you about the product features and possible applications of Eurol products. The information in this document is subject to change at any time without prior notice due to ongoing product research and development. The analysis data in this sheet contains typical values. Minor deviations, which can occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet has been compiled with great care, Eurol accepts no liability for damages resulting from any incompleteness and/or inaccuracies in the text. We always advise you to follow the manufacturer's instructions. The translations provided here are made using ChatGPT, an AI language model developed by OpenAI. While we strive to deliver accurate and useful translations, we cannot guarantee that all translations are error-free or always capture the correct context and nuances.



POWERING  
PERFORMANCE

# Eurol SHPD 15W-40 MF

Mineral motor oil for mixed fleet

Article number E100027 Version 3.0 14/04/2025

## Physical properties

Characteristic	Value/Result	ASTM Standard
Color	brown	
Density at 20°C	0.87 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	111.5 cSt	ASTM D 445
Viscosity, kinematic at 100°C	15.5 cSt	ASTM D 445
Viscosity Index	147	ASTM D 2270
Viscosity, dynamic (CCS)	4,396 cP	ASTM D 5293
Flash Point	242 °C	ASTM D 92
Pour point	-36 °C	ASTM D 97

**Eurol B.V., Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 88 250 22 00, info@eurol.com, eurol.com**

This document is intended to inform you about the product features and possible applications of Eurol products. The information in this document is subject to change at any time without prior notice due to ongoing product research and development. The analysis data in this sheet contains typical values. Minor deviations, which can occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet has been compiled with great care, Eurol accepts no liability for damages resulting from any incompleteness and/or inaccuracies in the text. We always advise you to follow the manufacturer's instructions. The translations provided here are made using ChatGPT, an AI language model developed by OpenAI. While we strive to deliver accurate and useful translations, we cannot guarantee that all translations are error-free or always capture the correct context and nuances.