

Eurol SHPD 25W-60

Mineral based SHPD motor oil

Article number E100044 Version 1.1 04/08/2025

Product information

Eurol SHPD 25W-60 is a robust engine oil, developed in accordance with the latest oil consumption and exhaust emission requirements, and meets all current quality standards for both European, American, and Japanese diesel and gasoline oils.

Eurol SHPD 25W-60 is ideally suited for heavy-duty diesel engines (trucks), but can also be used in gasoline, LPG, and light diesel engines, whether or not equipped with a turbo and/or catalyst and/or common rail.

Eurol SHPD 25W-60 amply meets the reduced limits regarding deposits on the piston crown, in the top piston ring groove, and the rest of the piston.

Due to its stability against high temperatures and aging, as well as the strong cleaning additives, Eurol SHPD 25W-60 ensures that the engine and the oil remain in good condition.

Wear is minimized, even under the most severe conditions, so that Eurol SHPD 25W-60 effortlessly lasts the prescribed replacement interval, regardless of the type of engine.

Performance level

API SL/CI-4

Recommended for use

- ACEA A3/B4
- ACEA E7
- Allison C-4
- Caterpillar ECF-1-A
- Caterpillar ECF-2
- CES 20076
- CES 20077
- CES 20078
- DDC Oil Category 2
- Detroit Diesel DDC 93K215
- Deutz DQC III-10
- DTFR 15B110 (MB 228.3)
- Global DHD-1
- JASO DH-1
- Mack EO-M Plus
- MAN M 3275
- MB 229.1
- MTU type 2
- Renault RLD
- Renault VI RLD-2
- Voith Class A
- Volvo VDS-3



Eurol SHPD 25W-60

Mineral based SHPD motor oil

Article number E100044 Version 1.1 04/08/2025

Physical properties

Characteristic	Value/Result	ASTM Standard
Color	brown	
Density at 20°C	0.89 kg/l	ASTM D 4052
Viscosity, kinematic at 40 °C	271.3 cSt	ASTM D 445
Viscosity, kinematic at 100 °C	24.5 cSt	ASTM D 445
Viscosity index	115	ASTM D 2270
Viscosity, dynamic (CCS)	10,872 cP	ASTM D 5293
Flash point	198 °C	ASTM D 92
Pour point	-30 °C	ASTM D 97