

Eurol Multifleet 15W-40

Mineral motor oil for mixed fleet

Article number F100046 Version 5.0 14/04/2025

Product information

Eurol Multifleet 15W-40 is developed in accordance with the latest oil consumption and exhaust emission requirements, and provides protection against viscosity increase and wear. The oil also has excellent cleaning properties.

Eurol Multifleet 15W-40 is ideally suited for mixed fleets, such as gasoline, LPG, and light diesel engines, whether or not equipped with a turbo and/or catalyst. Due to this broad applicability, the oil inventory for the user and reseller can be reduced.

Eurol Multifleet 15W-40 amply meets the reduced limits regarding deposits on the piston crown, on the top piston ring groove, and the rest of the piston.

Performance level

- API CH-4
- API SJ/CG-4

Recommended for use

- ACEA A2/B2
- ACEA A3/B3
- ACEA E2
- Allison C-4
- **API CF**
- Mack EO/L
- **MAN 271**
- MB 228.1
- MTU type 2
- Volvo VDS

Physical properties

Characteristic	Value/Result	ASTM Standard
Color	brown	
Density at 20°C	0.87 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	110.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	14.9 cSt	ASTM D 445
Viscosity Index	139	ASTM D 2270
Viscosity, dynamic (CCS)	5,421 cP	ASTM D 5293
Flash Point	214 °C	ASTM D 92
Sulfated Ash	1.2 wt%	ASTM D 874
Pour point	-30 °C	ASTM D 97