



Heavy duty diesel engine oils - Mineral

Eurol Multifleet 15W-40

Mineral motor oil for mixed fleet

Description

Eurol Multifleet 15W-40 has been developed according to the latest oil consumption and exhaust emission requirements and protects against oil thickening and wear. Besides, it has an excellent deterging capability.

Eurol Multifleet 15W-40 is especially suitable for mixed fleet applications like gasoline, LPG and light loaded diesel engines, whether or not turbo charged and/or with catalytic converter. Because of this broad applicability, this oil can reduce the stock level for the fleet owner and the retailer.

Eurol Multifleet 15W-40 amply fulfils the latest, strict norms regarding deposits on piston crowns, in top piston ring grooves and on the rest of the pistons.

Performance level

- API SJ/CG-4

Recommended for use

- API CF
- ACEA A2/B2
- ACEA A3/B3
- ACEA E2
- Allison C-4
- MB 228.1
- MAN 271
- Volvo VDS
- MTU type 2
- Mack EO/L

Physical properties

Colour	brown	
Density at 20°C	0.869 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	110.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	14.9 cSt	ASTM D 445
Viscosity Index	139	ASTM D 2270
Viscosity, dynamic (CCS)	5421 cP	ASTM D 5293
Base number	8.4 mg	ASTM D 2896
Sulphated ash	1.19 wt%	ASTM D 874
Flash point	214 °C	ASTM D 93
Pour point	-30 °C	ASTM D 97

Article number E100046
Version 5.0, 11-01-2022

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.