

# **Eurol Bediga 25W-60**

## Mineral motor oil for mixed fleet

Article number E100055 Version 3.0 14/04/2025

### **Product information**

Eurol Bediga 25W-60 is an engine oil that ensures optimal lubrication for older cars and light commercial vehicles with gasoline, LPG, and diesel engines.

Eurol Bediga 25W-60 can be used in engines equipped with turbocharging, multi-valve technology, and engines equipped with a catalytic converter.

Eurol Bediga 25W-60 offers excellent protection against wear of all engine components, which are also extremely well protected against rust and corrosion. Special dispersants keep soot and other dirt in suspension.

Eurol Bediga 25W-60 also contains special additives that ensure the oil does not thicken due to oxidation, even at high temperatures.

Due to the stable viscosity index improver, the viscosity will decrease very little, so Eurol Bediga 25W-60 continues to build a stable lubricating film between moving parts even after a long period.

#### Performance level

#### Recommended for use

API SG/CF-4

- MIL-L-2104D
- MIL-L-46152

# **Physical properties**

Characteristic	Value/Result	ASTM Standard
Color	brown	
Density at 20°C	0.88 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	248.3 cSt	ASTM D 445
Viscosity, kinematic at 100°C	23.0 cSt	ASTM D 445
Viscosity Index	114	ASTM D 2270
Viscosity, dynamic (CCS)	7,977 cP	ASTM D 5293
Flash Point	255 °C	ASTM D 92
Sulfated Ash	1.6 wt%	ASTM D 874
Pour point	-24 °C	ASTM D 97